

### Product Information

**Construction** - Solid Vinyl Tile (Luxury Vinyl Tile / LVT)

**Edge Detail** - Micro Bevel

**International Specifications** - ASTM F1700, Class III, Type B embossed surface

**Overall Thickness** - 3 mm (0.120 in.)

**Wear Layer Thickness** - 20 mil (0.02 in.)

**Factory Finish** - Polyurethane Protective Coating

**Installation** - Parterre Universal, #539P, Royal Epoxy

**Maintenance Options** - No waxing, buffing, sealers or finishes required

### Packaging

Size	Pieces per Carton/Coverage	Shipping Weight per Carton
6 in. x 36 in. (152 mm x 914 mm)	24 / 36 sq. ft. (3.34 m <sup>2</sup> )	42 lbs. (19 kg)
7.25 in. x 48 in. (184 mm x 1219 mm)	16 / 38.67 sq. ft. (3.59 m <sup>2</sup> )	45 lbs. (20 kg)
Vertu Only 18 in. x 18 in. (457.2 mm x 457.2 mm)	16 / 36 sq. ft. (3.34 m <sup>2</sup> )	42 lbs. (19 kg)

### Testing

ASTM F1700			
Performance	Test Method	Requirement	Performance vs. Requirement
Thickness	ASTM F386	Nominal $\pm 0.005$ in.	Meets
Size	ASTM F2055	$\pm 0.016$ in. per linear foot	Meets
Squareness	ASTM F2055	0.010 in. maximum	Meets
Residual Indentation	ASTM F1914	Average less than 8%	Meets
Flexibility	ASTM F137	$\geq 1.0$ in., no cracks or breaks	Meets
Dimensional Stability	ASTM F2199	0.020 in./lin. ft.	Meets
Static Coefficient of Friction/Slip	ASTM D2047	$\geq 0.5$	Meets
Chemical Resistance	ASTM F925	No more than slight change in surface dulling, attack or staining	Meets
Resistance to Heat	ASTM F1514	$\Delta E \leq 8$	Meets
Resistance to Light	ASTM F1515	$\Delta E \leq 8$	Meets
Additional Testing			
Static Load Resistance	ASTM F1914	Avg. < 8%	Meets
Fire Test Data – Flame Spread	ASTM E648	0.45 W/cm <sup>2</sup> or more Class 1	Meets
Fire Test Data – Smoke Evolution	ASTM E662	$\leq 450$	Meets
Certified Low Emitting Product	LEED EQ4.3	–	Meets
Certified Low Emitting Adhesive	LEED EQ4.1	–	Meets
Indoor Air Quality – Product	FloorScore®	–	Meets
Indoor Air Quality – Adhesive	FloorScore®	–	Meets
Indoor Air Quality	CHPS 01350	–	Meets

### Sustainability

#### WELL v1 Feature

<b>Air</b>	Feature 04 - VOC Reduction
	Feature 11 - Fundamental Material Safety
	Feature 25 - Toxic Material Reduction
<b>Mind</b>	Feature 97 - Material Transparency
	Feature 88 (Part 2) Biophilia I - Qualitative
	Feature 99 - Beauty and Design II

#### Vertu Ingrained

✓
✓
✓
✓
✓
✓

#### Contribution

Tested and third party certified by FloorScore® as complying with CDPH v1.2
Product is free of asbestos and added lead (Part 1)
Free of flame retardants (Part 2) and phthalates (Part 3)
Readily available Health Product Declaration® (HPD) to 1000 ppm
Products available that incorporate nature patterns
Patterns and colors to aid in wayfinding and spatial familiarity (Part 3)

#### WELL v2 Feature

<b>Air</b>	Feature X12 - Short Term Emission Control
	Feature X11 Long-Term Emission Control
	Feature X01 Fundamental Material Precautions
	Feature X10 Volatile Organic Compound
<b>Materials</b>	Feature X14 Material Transparency
	Feature M02 Access to Nature
	Feature C13 (Part 2) Accessibility and Universal Design

#### Vertu Ingrained

✓
✓
✓
✓
✓
✓

#### Contribution

Adhesives associated with product are tested and third party certified by FloorScore as complying with CDPH v1.2
Flooring is tested and third party certified by FloorScore as complying with CDPH v1.2
Product is free of asbestos
Free of flame retardants (Part 2) and phthalates (Part 3)
Readily available Health Product Declaration (HPD) to 1000 ppm
Products available that incorporate nature patterns
Patterns and colors to aid in wayfinding and spatial familiarity

#### LEED™ v4.1

BPDO - EPD
BPDO - Material Ingredient
Low Emitting Flooring
Low Emitting Adhesives
SCAQMD #1168 Compliant.
Adhesives meet <50 g/L requirement

#### Vertu Ingrained

Product Specific
HPD
Tested and third party certified by FloorScore as complying with CDPH v1.2
Tested and compliant to CDPH v1.2; Methylene Chloride and Perchloroethylene not intentionally added; FloorScore Certified Parterre Universal, #539P, Royal Epoxy – 0 g/L

### Limited Warranty

20-year Commercial Warranty when installed in strict accordance with the detailed instructions.

#### Visit [ParterreFlooring.com](http://ParterreFlooring.com)

for complete Product, Technical, Adhesives, Installation & Maintenance recommendations.

PT-1015-1122  
 ©2022 Parterre® is the property of AHF, LLC  
 FloorScore® is a registered trademark of the Resilient Floor Covering Institute. | LEED® is a registered trademark of the United States Green Building Council.

