

PRODUCT

Collections	QuickTrack 5mm Loose Lay
Descriptions	5mm Loose Lay luxury vinyl is simple to install and maintain with a specialized backing for sound absorption and comfort, providing traction to stay in place freely after installation.
Benefits	<ul style="list-style-type: none"> • Quick and easy installation • Water, scratch, stain and scuff resistant • Quiet and comfortable to walk on • Specialized backing for traction
Construction	Solid Vinyl Plank
International Specifications	ASTM F 1700, Class III, Type B – embossed surface
Product Thickness	5mm
Wear Layer Thickness	20 mil
Finish	Polyurethane protective coating with matte finish
Edge Type	Square
Adhesive	Parterre Universal Adhesive
Installation Type	Loose Lay; perimeter adhesive required (Full spread adhesive optional)
Warranty	20-Year Commercial Warranty

SIZE AND PACKAGING

Plank Sizes	7.25 in. x 48 in. • 10 pieces/carton • 23.33 sq. ft./carton • 40 lb./carton
Tile Sizes	12 in. x 24 in. • 10 pieces/carton • 20.02 sq. ft./carton • 34 lb./carton
Shipping Weight	Contact Customer Service: 888.338.1029 or info@parterreflooring.com

PERFORMANCE

	TEST	REQUIREMENTS	RESULT
Thickness	ASTM F 386	Nominal ± 0.0005 inch	Meets
Size	ASTM F 2005	± 0.016 inch per linear foot	Pass
Squareness	ASTM F 2055	0.010 inch max	Pass
Residual Indentation	ASTM F 1914	Average < 8%	Pass
Flexibility	ASTM F 137	≤ 1.0 inch, no cracks or breaks	Pass
Dimensional Stability	ASTM F 2199	0.02017 inch max.	Exceeds per liner foot
Static Coefficient of Friction/Slip	ASTM D 2047	≥ 0.50	Pass
Chemical Resistance	ASTM F 925	No more than slight change in surface dulling, attack or stain	Meets or Exceeds
Resistance to Heat	ASTM F 1514	ΔE ≤ 8	Pass
Resistance to Light	ASTM F 1515	ΔE ≤ 8	Pass
Static Load Limit	ASTM F 970	No visual apparent Indentation	250 psi
Fire Test Data – Flame Spread	ASTM E 648	0.45 watt/cm ² or more Class I	Meets
Fire Test Data – Smoke Evolution	ASTM E 662	≤ 450	Meets
Indoor Air Quality	FloorScore™	–	Meets
Indoor Sound Transmission Test	ASTM E 492	–	IIC: 62 (test condition: 6" concrete slab with drop ceiling)

ASTM F 1700

SUPPLEMENTARY

TECHNICAL INFORMATION

For warranties, installation and maintenance instructions, contact your Parterre Sales Representative or visit our website at: www.parterreflooring.com

