

## **SPECIFICATIONS** SUMMARY 2.5MM TILE AND PLANK

$\overline{}$	$\overline{}$	$\overline{}$	$\overline{}$	 വ	_

Collections	Elemental
Construction	Solid Vinyl Tile and Plank
International Specifications	ASTM F 1700, Class III, Type B – embossed surface
Product Thickness	2.5mm (0.098 in.)
Wear Layer Thickness	0.5mm (0.020 in.)
Finish	Polyurethane protective coating
Adhesive	Parterre Adhesive #539P, #549P, Royal Epoxy
Maintenance Options	Polish • No Polish – Spray Buff/No Buff
Warranty	10-Year Limited Commercial Warranty (to view, visit parterreflooring.com > Technical > Warranties)

## SIZE AND PACKAGING

Tile Sizes	18 in. x 18 in. • 16 pieces/carton • 36 sq. ft./carton • 35 lb./carton 12 in. x 24 in. • 18 pieces/carton • 36 sq. ft./carton • 35 lb./carton	
Plank Sizes	4 in. x 36 in. • 36 pieces/carton • 36 sq. ft./carton • 35 lb./carton 6 in. x 36 in. • 24 pieces/carton • 36 sq. ft./carton • 35 lb./carton	
Shipping Weight	Contact Customer Service: 888.338.1029 or info@parterreflooring.com	

## **PERFORMANCE**

TEST	REQUIREMENTS	RESULT
ASTM F 386	Nominal ± 0.0005 in.	Pass
ASTM F 2055	± 0.016 in. per linear foot	Pass
ASTM F 2055 0.010 in. max		Pass
ASTM F 1914	Average < 8%	Pass
ASTM F 137	≤ 1.0 in., no cracks or breaks	Pass
ASTM F 2199	0.020 in. per linear foot	Pass
ASTM D 2047	≥ 0.50	Pass
ASTM F 925	No more than slight change in surface dulling, attack or stain	Pass
ASTM F 1514	ΔE ≤ 8	Pass
ASTM F 1515	ΔE ≤ 8	Pass
ASTM E 648	0.45 watt/cm <sup>2</sup> or more Class I	Pass
ASTM E 662	≤ 450	Pass
LEED EQ4.3	-	Meets Guidelines
LEED EQ4.1	-	Meets Guidelines
FloorScore™	-	Meets Guidelines
CHPS 01350	-	Meets Guidelines
	ASTM F 2055 ASTM F 2055 ASTM F 1914 ASTM F 137 ASTM F 2199 ASTM D 2047 ASTM F 925 ASTM F 1514 ASTM F 1515 ASTM E 648 ASTM E 662 LEED EQ4.3 LEED EQ4.1 FloorScore™	ASTM F 2055 $\pm$ 0.016 in. per linear foot  ASTM F 2055 0.010 in. max  ASTM F 1914 Average < 8%  ASTM F 137 $\leq$ 1.0 in., no cracks or breaks  ASTM F 2199 0.020 in. per linear foot  ASTM D 2047 $\geq$ 0.50  ASTM F 925 No more than slight change in surface dulling, attack or stain  ASTM F 1514 $\Delta$ E $\leq$ 8  ASTM F 1515 $\Delta$ E $\leq$ 8  ASTM E 648 0.45 watt/cm² or more Class I  ASTM E 662 $\leq$ 450  LEED EQ4.3  LEED EQ4.1  FloorScore <sup>TM</sup> -

## **TECHNICAL INFORMATION**

Installation Technical Manual	Visit parterreflooring.com > Technical > Installation > Tile, Plank and Sheet
Maintenance Technical Manual	Visit parterreflooring.com > Technical > Maintenance > General

version 9.12.2017