

### Product Information

**Construction** - Stone Polymer Composite (SPC)

**Edge Detail** - Micro Bevel

**International Specifications** - ASTM F 3261, Class I, Type B, Grade 1, Backing Class B

**Overall Thickness** - 6 mm (0.24 in.) with attached pad for acoustic performance

**Wear Layer Thickness** - 20 mil (0.02 in.)

**Factory Finish** - UV Cured Urethane with Ceramic Bead

**Installation** - Floating - Optional Glue Down

**Maintenance Options** - No waxing, buffing, sealers or finishes required

### Packaging

| Size                                  | Pieces per Carton/Coverage                | Shipping Weight per Carton |
|---------------------------------------|---|----------------------------|
| 71 in. x 60 in. (180.34 mm x 1524 mm) | 10 / 29.53 sq. ft. (2.74 m <sup>2</sup> ) | 63 lbs. (28.58 kg)         |

### Testing

| ASTM F1700                          |             |   |                             |
|-------------------------------------|-------------|---|-----------------------------|
| Performance                         | Test Method | Requirement   | Performance vs. Requirement |
| Thickness                           | ASTM F387   | Nominal ±0.008 in.  | Meets                       |
| Size                                | ASTM F2055  | ± 0.016 in. per linear foot                                       | Meets                       |
| Squareness                          | ASTM F2055  | 0.010 in. maximum   | Meets                       |
| Residual Indentation                | ASTM F1914  | ≤ 0.007 in.   | Meets                       |
| Dimensional Stability               | ASTM F2199  | 0.2%/in. Ft.  | Meets                       |
| Static Coefficient of Friction/Slip | ASTM D2047  | ≥ 0.5   | Meets                       |
| Chemical Resistance                 | ASTM F925   | No more than slight change in surface dulling, attack or staining | Meets                       |
| Resistance to Heat                  | ASTM F1514  | ΔE ≤ 8  | Meets                       |
| Resistance to Light                 | ASTM F1515  | ΔE ≤ 8  | Meets                       |
| Additional Testing                  |             |   |                             |
| Static Load Resistance              | ASTM F970*  | ≤ 0.005 in.   | Meets                       |
| Fire Test Data – Flame Spread       | ASTM E648   | 0.45 W/cm <sup>2</sup> or more Class 1                            | Meets                       |
| Fire Test Data – Smoke Evolution    | ASTM E662   | ≤ 450   | Meets                       |
| Certified Low Emitting Product      | LEED EQ4.3  | –   | Meets                       |
| Certified Low Emitting Adhesive     | LEED EQ4.1  | –   | Meets                       |
| Indoor Air Quality – Product        | FloorScore® | –   | Meets                       |
| Indoor Air Quality – Adhesive       | FloorScore® | –   | Meets                       |
| Indoor Air Quality                  | CHPS 01350  | –   | Meets                       |

### Sustainability

#### WELL v1 Feature

|             |   |
|-------------|---|
| <b>Air</b>  | Feature 04 - VOC Reduction                    |
|             | Feature 11 - Fundamental Material Safety      |
|             | Feature 25 - Toxic Material Reduction         |
| <b>Mind</b> | Feature 97 - Material Transparency            |
|             | Feature 88 (Part 2) Biophilia I - Qualitative |
|             | Feature 99 - Beauty and Design II             |

#### Individuality™ Thrive™

|   |
|---|
| ✓ |
| ✓ |
| ✓ |
| ✓ |
| ✓ |
| ✓ |

#### Contribution

|   |
|---|
| Tested and third party certified by FloorScore® as complying with CDPH v1.2 |
| Product is free of asbestos and added lead (Part 1)                         |
| Free of flame retardants (Part 2) and phthalates (Part 3)                   |
| Readily available Health Product Declaration® (HPD) to 1000 ppm             |
| Products available that incorporate nature patterns                         |
| Patterns and colors to aid in wayfinding and spatial familiarity (Part 3)   |

#### WELL v2 Feature

|                  |   |
|------------------|---|
| <b>Air</b>       | Feature X12 - Short Term Emission Control               |
|                  | Feature X11 Long-Term Emission Control                  |
|                  | Feature X01 Fundamental Material Precautions            |
|                  | Feature X10 Volatile Organic Compound                   |
| <b>Materials</b> | Feature X14 Material Transparency                       |
|                  | Feature M02 Access to Nature                            |
| <b>Mind</b>      | Feature C13 (Part 2) Accessibility and Universal Design |
|                  |   |
| <b>Community</b> |   |

#### Individuality™ Thrive™

|   |
|---|
| ✓ |
| ✓ |
| ✓ |
| ✓ |
| ✓ |
| ✓ |
| ✓ |
| ✓ |

#### Contribution

|  |
|--|
| Adhesives associated with product are tested and third party certified by FloorScore as complying with CDPH v1.2 |
| Flooring is tested and third party certified by FloorScore as complying with CDPH v1.2                           |
| Product is free of asbestos  |
| Free of flame retardants (Part 2) and phthalates (Part 3)  |
| Readily available Health Product Declaration (HPD) to 1000 ppm   |
| Products available that incorporate nature patterns  |
| Patterns and colors to aid in wayfinding and spatial familiarity   |

#### LEED™ v4.1

|                                    |
|------------------------------------|
| BPDO - EPD                         |
| BPDO - Material Ingredient         |
| Low Emitting Flooring              |
| Low Emitting Adhesives             |
| SCAQMD #1168 Compliant.            |
| Adhesives meet <50 g/L requirement |

#### Individuality™ Thrive™

|  |
|--|
| Product Specific   |
| HPD  |
| Tested and third party certified by FloorScore as complying with CDPH v1.2   |
| Tested and compliant to CDPH v1.2; Methylene Chloride and Perchloroethylene not intentionally added; FloorScore Certified Parterre Universal, #539P, Royal Epoxy – 0 g/L |

### Limited Warranty

20-year Commercial Warranty when installed in strict accordance with the detailed instructions.

#### Visit [ParterreFlooring.com](http://ParterreFlooring.com)

for complete Product, Technical, Adhesives, Installation & Maintenance recommendations.

PT-1014-1122  
 ©2022 Parterre® is the property of AHF, LLC  
 FloorScore® is a registered trademark of the Resilient Floor Covering Institute. | LEED® is a registered trademark of the United States Green Building Council.

