

UNIVERSAL

Transitional Pressure Sensitive® Adhesive for Luxury Vinyl Tile and Plank

Versatile for nearly any flooring installation, Universal is a pressure sensitive adhesive that is strong with moisture, guaranteeing up to 99% RH when used in new construction and up to 95% RH for use in pre-existing buildings. Universal is FloorScore® certified and Color Ready™ for an easy installation process.



Features:


- Tolerates up to 95% RH Moisture for existing construction, and up to 99% new construction.*
- Changes color when ready with ColorReady™ technology
- Greater flexibility for large installations
- High strength, water resistant bond
- High tack, fast grab and extended working time
- LEED v4 contributing (CDPH v1.2)
- Shelf Life: 2 Years

Working Time:

Time Allowance: Allow 12 hours of working time for product installation

Color change: Typically takes 30-60 minutes before transitioning from mint green to teal.

Recommended Tools:



| Weights/Spread Rate | | | | Maximum Moisture and pH Levels | |
|---------------------|----------|------------------------|----------------------------|--------------------------------|-----------|
| Size | Weight | Over Porous Substrates | Over Non-porous Substrates | RH Max | pH Range |
| 1 gal. | 9.25 lb. | 180 sq. ft./gal. | 260 sq. ft./gal. | 95-99%* | up to 9.9 |
| 4 gal. | 37 lb. | 720 sq. ft./gal. | 1,040 sq. ft./gal. | | |

For installation technical manual, visit: parterreflooring.com/technical

For more information contact us at parterreflooring.com or 888.338.1029.

