

Light Reflectivity

Luxury Flooring

Unfazed™

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g., 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°: 0° or 0°: 45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values greater than 25% can contribute to LEED® Interior Lighting Credit.

Value	SKUs
0-9	--
10-14	--
15-19	5AP07641, 5AP10641
20-24	5AP06641
25-29	5LP01641, 5AP02641
30-34	5LP03641
35-39	5AP11641
40-44	--
45-49	--
50-54	--
55-59	--
60-64	--
65-69	--
70-74	--

ParterreFlooring.com

for complete Product, Technical, Adhesives, Installation, and Maintenance recommendations.

LEED® is a registered trademark of the United States Green Building Council.

©2024 All trademarks are owned by AHF, LLC, or its subsidiaries or affiliates.